

Apollo and Apollo Hi-Riser Order Form



Standard Selections:

Liftoff:

Select One

- Standard Apollo
- Apollo Hi-Riser



Standard Liftoff



Hi-Riser Liftoff
Shown with direct
mount flange

Outlet:

Select One

- 2.5" NH standard
- 2.5" special thread

Specify thread code or size _____

Nozzles for Standard 2 1/2" threaded NH outlet: (specify thread if other than NH) _____

Select One

- No Nozzle

Fog Nozzles:

Select One

- 5160 Akromatic 1250gpm (4800lpm) @ 80 psi (5.5 bar)
- 5160 Akromatic 1000gpm (3800lpm) @80 psi (5.5 bar)
- 5147 Excel Adjustable nozzle 500-800-1000 gpm (1900-3000-3800lpm) @75psi(5 bar)
- 4475 AkroFoam self-educing nozzle 350-500-750-1000gpm (1330-1900-2850-3800lpm) with pickup hose and metering head

Straight Bore Tips:

Select One

- 2499 Quad Stack Tip Set (requires 3488 or 3485 shaper)
- 2498 Triple Stack Tip Set (requires 3488 or 3485 shaper)
- 0489 Deluge Tip, specify discharge size _____ (requires 3488 or 3485 shaper)

Stream Shaper:


Select One

- 3485 2.5" x 2.5" mini shaper, 4" long
- 3488 2.5" x 2.5" standard shaper 10.5" long
- No Shaper

Direct Mount Flange:

Select One

- YES
- NO



Standard

Hi-Riser



LDH Single Inlet

Ground Base Inlet:

Select One

- Dual Inlet 2x - 2.5" NH unless otherwise specified _____
- LDH Single inlet threaded female swivel. Specify Thread Size _____
- LDH Single inlet Storz fitting. Specify Size _____
- No Ground Base



Dual Inlet