

HEN

BLADE 160

Combination Smoothbore Nozzle




Overview

The HEN BLADE combination smoothbore nozzle redefines fire attack by combining the reach and penetration of a traditional smoothbore with the versatility of an in-line blade pattern. With a simple quarter turn, firefighters can transition from a tight solid stream to a wide, high-impact blade stream, delivering large water droplets for maximum efficiency, improved cooling, and enhanced control.

Specifications

	IMPERIAL	METRIC
Target Flow	160 gpm	650 lpm
Target Pressure	50 psi	4 bar
Blade Pattern Angle	22°	22°
Weight	1.7 lb	0.77 kg
Length	6.6 in.	168 mm
Width	3.2 in.	81 mm

Coverage



Features

- Quarter-turn from wide blade pattern to solid tight pattern
- Hard-coat anodized aluminum construction
- Available with 1.5" NH and 1.5" NPSH threads
- Full-time swivel
- NFPA 1960/1964 compliant
- 5-Year Warranty

Flow Rates

PRESSURE PSI (BAR)	FLOW RATE GPM (LPM)
30 (2.1)	124 (470)
40 (2.8)	143 (543)
50 (3.4)	160 (607)
60 (4.1)	176 (665)
70 (4.8)	190 (719)



NFPA
COMPLIANT